

All square tube 12 gauge galvanized steel with 0.4375" holes on either 1" centers or drilled as needed.

- (1) H skid, cross bar 2" x 2" x 30" long.
- (1) H skid, vertical stub 2" x 2" x 12" long.
- (1) Vertical mast 2.25" x 2.25" x 96" long.
- (1) Sleeve 2.5" x 2.5" x 36" long.

Sign mounting hardware: 5/16" (0.3125") stainless steel or grade 5 zinc plated bolts and washers, nylon insert lock nut, and nylon washers against sign face.


APPROVED

DATE OF REV.

12/1/05

NCHRP 350 COMPLIANT PORTABLE SIGN STAND FOR **DETOUR ASSEMBLY WITH 8' MAST**





All square tube 12 gauge galvanized steel with 0.4375" holes on either 1" centers or drilled as needed. (2) Vertical masts - 1.75" x 1.75" x 90.5" long. (2) Sleeves - 2" x 2" x 36" long.

(2) Horizontal legs - 1.5" x 1.5" x 60" long.

(2) Legs, vertical stubs - 1.5" x 1.5" x 1.2" long.
Sign mounting hardware: 5/16" (0.3125") stainless steel or grade 5 zinc plated bolts and washers, nylon insert lock nut, and nylon washers against sign face.


APPROVED

DATE OF REV.

7/15/05

NCHRP 350 COMPLIANT PORTABLE SIGN STAND FOR WORK ZONE SPEED LIMIT





All square tube 12 gauge galvanized steel with 0.4375" holes on either 1" centers or drilled as needed.

- (1) H skid, cross bar 2" x 2" x 30" long.
- (1) H skid, vertical stub 2" x 2" x 12" long.
- (1) Vertical mast 2.25" x 2.25" x 72" long.
- (1) Sleeve 2.5" x 2.5" x 36" long.

Sign mounting hardware: 5/16" (0.3125") stainless steel or grade 5 zinc plated bolts and washers, nylon insert lock nut, and nylon washers against sign face.

APPROVED

DATE OF REV.

7/15/05

NCHRP 350 COMPLIANT PORTABLE SIGN STAND FOR DETOUR ASSEMBLY

